PREMIUM SPRAY PAINTS AND ENAMELS

PREMIUM ENAMEL

- Quick-drying multi-purpose enamels for interior/exterior use
- Superior coverage, durability and rust-resistant finish
- Resists chipping and peeling
- Use on metal, wood, plaster and masonry surfaces that have been primed with primer below
- Dry time: 8-12 minutes to touch
- Case contains: 6 - 16 oz (10.5 oz net wt) cans - **Sold by case only** (148 cs per pallet)



*MFR # 419-0926
Gloss Forest Green
Control # 5687109

OSHA
*MFR # 419-0930
Danger Orange
Control # 5687113

*MFR # 419-0931
Gloss Rich Brown
Control # 5687114

*MFR # 419-0932
Gloss Clear Coat
Control # 5687115

*MFR # 419-0938
Satin Black
Control # 5687118

*MFR # 419-0940
Gloss Machinery Gray
Control # 5687119

*MFR # 419-0941
Dull Aluminum
Control # 5687120

OSHA
*MFR # 419-0943
Gloss Medium Gray
Control # 5687122

OSHA
*MFR # 419-0944
Gloss Light Green
Control # 5687123

WARNING: This product can expose you to chemicals including ethylbenzene which is known to the State of California to cause cancer, and toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



PREMIUM PRIMER

- Fast-drying formula seals, primes, adds protection against rust for interior/exterior use
- Improves adhesion of the color coat and provides base for a smoother finish
- Dry time: 8-12 minutes to touch
- Case contains: 6 - 16 oz (10.5 oz net wt) cans - **Sold by case only** (148 cs per pallet)

PRIMER
*MFR # 419-0935
Gray Metal Primer
Control # 5687136

WARNING: Cancer and Reproductive Harm-
www.P65Warnings.ca.gov

* Manufacturer Discontinued - Limited Quantity Available

G. F. Lasswell Company, Inc.
Lasswell
Manufacturers' Redistributor

713.644.4313 / 800.666.4313 | (fax) 713.644.0130 / 877.644.0130
masters@lasswell.com | www.lasswell.com

©2026 G.F. Lasswell Company, Inc. All Rights Reserved. 212-10-2575-1-2

INVERTED PAINT

- Fast-drying water based formula
- Top-down-only valve designed for use with wands below or manual application
- Indoor/outdoor use to mark hazards, playing fields, landscaping, surveying, construction areas, underground utilities
- For use on grass, gravel or paved surfaces
- APWA (American Public Works Association) and fluorescent colors available
- For use with wands 419-4831 or 419-4832 below
- Dry time: 30 minutes to touch
- Case contains: 12 - 20 oz (17 oz net wt) cans - **Sold by case only** (72 CS per pallet)

FLUORESCENT COLORS

*MFR # 419-4801
Fluorescent Blue
Control # 5697100

APWA COLORS

Temporary survey
*MFR # 419-4854
APWA Pink
Control # 5697124

Reclaimed or non-potable water
*MFR # 419-4855
APWA Purple
Control # 5697125

Electric Lines
*MFR # 419-4857
APWA Red
Control # 5697127



* Manufacturer Discontinued - Limited Quantity Available

WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov

WANDS

- **For use with only inverted spray paints above**
- Pistol trigger handle
- Tool free assembly
- **Sold by each**

MFR #	SIZE	CONTROL #
*419-4831	34.5" LENGTH	5697190
*419-4832	12.5" LENGTH	5697191



419-4831



419-4832

Inverted Field Marking, Pavement & Striping Spray Paints Available-Please call for details.

* Manufacturer Discontinued - Limited Quantity Available

G. F. Lasswell Company, Inc.
Lasswell
Manufacturers' Redistributor

713.644.4313 / 800.666.4313 | (fax) 713.644.0130 / 877.644.0130
masters@lasswell.com | www.lasswell.com

©2026 G.F. Lasswell Company, Inc. All Rights Reserved. 212-10-2575-1-2

ROOF ACCESSORIES PAINT

- Flat finish, rust-resistant spray that camouflages and protects gutters, flashing, vents, soil stacks, and other roof accessories
- For use on metal, masonry, wood, vinyl, and PVC (not for use on asphalt shingles)
- Dry time: 8-12 minutes to touch
- Case contains: 6 - 16 oz (10.5 oz net wt) cans - **Sold by case only** (148 cs per pallet)



*MFR # 419-4862
Cedar
Control # 5687151

*MFR # 419-4868
Slate
Control # 5687154

*MFR # 419-4872
Hickory
Control # 5687156

WARNING: Cancer and Reproductive Harm-
www.P65Warnings.ca.gov

HIGH HEAT PAINT

- Formulated to withstand temperatures of 1200°F with excellent adhesion
- Use on all indoor and outdoor surfaces exposed to high temperatures, including radiators, barbecues, stoves, car exhaust manifolds, engines, boilers, heaters and steam pipes
- Dry time: 1 hour to touch
- Case contains: 6 - 16 oz (12 oz net wt) cans - **Sold by case only** (148 cs per pallet)



*MFR # 419-0981
Black
Control # 5687166

G. F. Lasswell Company, Inc.
Lasswell
Manufacturers' Redistributor

713.644.4313 / 800.666.4313 | (fax) 713.644.0130 / 877.644.0130
masters@lasswell.com | www.lasswell.com

©2026 G.F. Lasswell Company, Inc. All Rights Reserved. 212-10-2575-1-2

COLD GALVANIZE (95% ZINC)

- Complete zinc metal spray which rustproofs any metal surface with thorough protection that lasts for years
- It is equivalent to a hot galvanizing treatment as it fuses and adheres to all metal surfaces, stopping corrosion immediately
- Coated surfaces can be welded safely without fire or fumes
- Resistant to abrasion, cracking or peeling, and oxidation
- Heat resistant up to 400° F & does not contain lead
- Conforms to military specifications MIL-P-21035 USAF, MIL-P-26915A, MIL-P-46105 for primer coatings and galvanizing repair
- Case contains: 6 - 16 oz (12 oz net wt) cans - **Sold by case only** (148 CS per pallet)



MFR #	CONTROL #
419-T3408	5697170

WARNING: This product can expose you to chemicals including ethylbenzene which is known to the State of California to cause cancer, and toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

G. F. Lasswell Company, Inc.
Lasswell
Manufacturers' Redistributor

713.644.4313 / 800.666.4313 | (fax) 713.644.0130 / 877.644.0130
masters@lasswell.com | www.lasswell.com

©2026 G.F. Lasswell Company, Inc. All Rights Reserved. 212-10-2575-1-2