

Specifications

FRAMESET	Frame	6061 Triple-Butted Aluminum alloy frame, integrated cable routing, internal battery, flat mount disc, rack and fenders compatible
	Fork	6061 Aluminum alloy, internal brake routing, 12x100mm thru-axle, 1-1/4" to 1-1/8" tapered steerer
	Sizes	S: 5'1-5'8, M: 5'5-6'0
ELECTRONICS	Motor Hub	350W, Peak 600W, 45Nm
	Battery	36V, 9.8Ah, 352.8Wh
	Cell	Samsung 21700
	Charger	36V, 2.0A, Operates on 100V-240V AC, 50-60Hz, 0-80% 4 Hours, 0-100% 6 Hours
	Control Panel	Battery indicator, PAS indicator, Auto headlight, Auto brightness control
	Sensor	Torque sensor
	Throttle	N.A.
	Headlight	Light sensing, 6V/3W/45Lux high-output integrated LED, Adjustable angle
	Security	Apple® Find My™
SPEED & RANGE	Top Speed	20 MPH, Class 1
	Max Range	Up to 52 Miles
	Pedal Assist	Level 1 - 5 (Eco, Tour, Normal, Sport and Turbo)
DRIVETRAIN	Chainrings	PROWHEEL Pro Aluminum alloy, 42T narrow wide chainring
	Crankset	Aluminum alloy, 165mm
	Cassette	8-speed, 11-32T
	Chain	KMC Z8.3
	Rear Derailleur	SHIMANO M310-8
	Shift Lever	SHIMANO M315-8
BRAKE	Brake	TEKTRO HD-R280 hydraulic disc brake
	Rotors	160mm front and rear
	Brake Levers	TEKTRO HD-R280 Aluminum alloy, with adjustable reach
WHEEL	Rim	700c disc, Double-wall Aluminum alloy, Pinned (F) 24 hole / (R) 28 hole
	Tire	700 X 40c Ebike puncture resistant tires
	Front Hub	NOVATEC Aluminum alloy J-hook disc hub, 12x100mm thru-axle
COCKPIT	Handlebar	6061 Aluminum alloy, Ø31.8mm, 660mm
	Grips	VELOTRIC ergonomic comfort grips
	Stem	6061 Aluminum alloy, 3D-forged alloy, 8-degree rise, 31.8mm clamp, Garmin mount compatible
	Saddle	Velotric Comfort, Customized by SELLE ROYAL
	Seatpost	6061 Aluminum alloy, 30.9x300mm
SUPPORTS	Pedals	Plastic
	Kickstand	Aluminum alloy
	Phone Mount	Adapt GoPro/Garmin
Weight	Bike Weight	36 lbs
LOAD	Max Bike Load	330 lbs