

HoistCam[™] Armored Dome HC180i (Industrial Series)

The HoistCam[™] HC180i from Netarus is an armored dome rapidly deployable wireless video night/day camera platform. The HC180i is a cost effective design, which is wired into external power source such as an external battery pack. HoistCam places the eyes of the crane operator anywhere on the job. Safety is increased, and efficiency improved by making instant visual information available to those who need it.



View from HoistCam Monitor

FEATURES

- Weatherproof camera with magnetic mount, wireless transmitter and camera
- 2.4Ghz directional wireless antenna and receiver
- Base magnets to mount to any magnetic surface
- 9.7in display with heavy duty RAM[®] suction cup mount
- Impact resistant polycarbonate armored dome
- Power source: 12VDC (external battery or wired)
- Storage temperatures: -10°C to +50°C
- Operating temperatures: -40°C to +50°C
- Safety lanyard and recyclable storage case
- Dimensions: 9" x 8" x 7" (with camera)
- Weight: Approximately 9lbs

OPTIONAL UPGRADES

- External battery pack for camera
- HoistCam Director Monitoring and recording
- Audio monitoring from microphone in HoistCam and audio monitoring from HoistCam Director MDVR
- U-bolt or permanent display mount
- Remote power key FOB for power management

Increases Safety & Productivity 20%+*

Rapidly Deployable Wireless Camera HoistCam Armored Dome HC180i (Industrial Series)

Magnetic Mounting System





Reusable Packaging (Cardboard Box)

©2018 Netarus, LLC. HoistCamTM is a trademark of Netarus. Netarus, LLC is constantly developing product improvements. We reserve the right to modify product design and specifications without notice and without incurring any obligation. * - see www.hoistcam.com/casestudy for referenced case studies.