LOAD RESTRAINT NET

QUALITY RESTRAINING SYSTEMS

Many avoidable incidents occur each year due to unrestrained vehicle loads, it is not only good practice to securely cover all loads but a legislative requirement¹.

Minecorp Load Restraint Nets suit most tray or tubs and are perfect for restraining tools, luggage and any other awkward loads. All nets have a maximum lashing capacity of 250KG's when used alone. If higher capacities are required it is advisable to add extra lashing straps².

Minecorp nets are manufactured with ultra violet (UV) stable heavy duty 38mm polypropylene webbing in a tight weave pattern which provides high grip and security to the cargo being restrained. The flat webbing design spreads the load so the surface of the load is not damaged, while the multiple eyelet design throughout the webbing allows the tie down straps to be better placed for maximum ease and safe holding. The tie down straps use 25mm heavy duty webbing, 600KG rated zinc plated high tensile cam buckles, 600KG rated quick connect carabineers to connect through the eyelets with ease, and 1200KG rated polyethylene coated sewn in hooks.

The Minecorp nets are supplied with a compact carry bag for ease of storage. Nets are available in a range of sizes to suit various applications, refer to the selection chart.









- 1. Legislative Requirement: Individual state and local government requirements.
- 2. Extra Lashing Straps: Refer to extra strap manufactures specifications for load capacities.



LOAD RESTRAINT NET

PRODUCT NUMBER

- M80000037/S : Single Cab Tray Service Body (1800mm x 900mm)
- M80000039/S : Single/Extra Cab Tray Body (1800mm x 2400mm)
- M80000038/S: Dual Cab Tub Body (1400mm x 1400mm)
- M80000042/S: DUAL CAB TRAY BODY (1800mm x1600mm)

FEATURES

- Suits Minecorp trays, service units and roll over protection bar locations
- 250KG lashing capacity when used alone
- UV stable for durability
- Multiple eyelet design

- Tie down straps included
- High strength grip design (Nominal gap between webbing is 60mm x 60mm)
- Compact carry bag included

NOTE: Minecorp recommend the use of a rubber load mat as they can more than halve the number of lashings needed providing a higher combination of load carrying safety (National Transport Commission of Australia, Load Restraint Guide).



QUALITY RESTRAINING SYSTEMS SELECTION CHART

PART NUMBER	WIDTH	LENGTH	NON ROPS	ROPS	NO. OF WEBBINGS	NO. OF TIE DOWN EYELETS	NO. OF TIE DOWN STRAPS	NET WEIGHT (KG)
M80000037/S	1800	900	1/2 TrayService Unit	1/2 TrayService Unit	29	96	6	4.1
M80000038/S	1400	1400	• Dual Cab (Tub Body)	-	30	117	4	3.75
M80000039/S	1800	2400	Single CabExtra Cab	-	44	188	8	7.0
M80000042/S	1800	1600	• Dual Cab	-	36	147	6	4.4

