



1. PRODUCT AND COMPANY

Product Identifier: Greenheart Lumber and Piling (Wood Dust)

General Use: Marine and Outdoor Structural Lumber, Hardwood Dust generated by cutting or abrasion

MANUFACTURER:

Untreated Wood Products, Inc.
 9820 Blue Grass Rd
 Philadelphia, PA 19114
 Phone: (267) 498-9997
 Fax: (845) 244-8400

EMERGENCY TELEPHONE NUMBERS:

(860) 415-3767

2. COMPOSITION / INFORMATION ON INGREDIENTS

| HAZARDOUS INGREDIENTS | PERCENT | CAS # | EXPOSURE LIMITS (mg/m3) | | |
|-----------------------|---------|-------|----------------------------|-----------|-------------|
| | | | OSHA-8 Hour PEL | ACGIH-TLV | ACGIH-STEL |
| Wood Dust | | NA | 1.0 (Dicorynia guianensis) | 5.0 (TWA) | 10.0 (STEL) |

3. HAZARDS IDENTIFICATION

Inhalation: Airborne treated, or untreated wood dust may cause nose, throat or lung irritation. Various species of untreated wood dust can elicit allergic respiratory response in sensitized persons.

Eye Contact: Treated or untreated wood dust may cause eye irritation.

Skin Contact: Handling wood may result in skin exposure to splinters. Prolonged and/or repeated contact with treated or untreated wood dust may result in mild irritation. Various species of untreated wood dust can elicit allergic type skin irritation in sensitized persons.

Ingestion: Not anticipated to occur. A single ingestion of a very large dose of treated wood dust may require immediate medical attention.

Chronic Wood Dust (treated or untreated) Effects: Wood dust, depending on species, may cause dermatitis on prolonged, repetitive contact. May cause respiratory sensitization and/or irritation.

4. FIRST AID MEASURES

Inhalation: Remove from wood dust exposure. If breathing has stopped administer artificial respiration. Seek medical aid if symptoms persist.

Eye Contact: Gently flush any particles from the eyes with large amounts of water for at least 15 minutes. DO NOT RUB THE EYES. Seek medical aid if irritation persists.

Skin Contact: Rinse wood dust off with water. DO NOT RUB. Once the skin is free of the wood dust, wash thoroughly with soap and water. Seek medical aid if severe irritation develops.

Ingestion: Rinse the victim's mouth out with water. Induce vomiting if directed by a physician or Poison Control Center.

5. FIRE FIGHTING MEASURES

Flash Point: NA **Lower Explosive Limit:** NA

Auto-ignition: Variable (400-500F) **Upper Explosive Limit:** NA

Extinguishing Agents: Water, CO2, Sand

January 1, 2020

5. FIRE FIGHTING MEASURES (CONT.)

Fire-Fighting Procedures: This product resists burning. Fire from a separate fuel source may be intense enough to cause ignition of the Wood Boards, standard fire fighting procedures should be followed. Wear complete fire service protective equipment, including full-face NIOSH/NFPA – approved self-containing breathing apparatus.

Fire and Explosion Hazard: High airborne levels of wood dust may burn rapidly in the air when exposed to an ignition source. Wood dust is strong to severe explosion hazard if a dust “cloud” contains an ignition source.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Sweep or vacuum spills for recovery or disposal, avoid creating dust conditions. Provide good ventilation where dust conditions may occur. Place recovered wood dust in a container for proper disposal.

Waste Disposal: See Section 13.

7. HANDLING AND STORAGE

Storage Conditions: Protect from physical damage. Maintain good housekeeping.

Caution: Whenever possible, sawing or machining treated or untreated wood should be performed outdoors to avoid accumulations of airborne wood dust. Wash hands thoroughly before eating, drinking, using tobacco products, and/or using restrooms.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection: None normally required. When sawing or cutting treated or untreated wood, wear a NIOSH approved N95 or better dust mask.

Eye Protection: Wear safety glasses with side shields or safety goggles when sawing or cutting.

Skin/Foot Protection: Leather or comparable gloves to prevent splinters. Long sleeve shirt, pants and steel-toed shoes when handling treated or untreated wood.

Ventilation: Saw, cut or machine wood outdoors or in well ventilated areas. Ventilation should be sufficient to maintain inhalation exposures below OSHA PEL for particulates.

Other Protective Equipment: Wear ear plugs or muffs when using power tools.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|----------------------------|-------|-------------------------------------|------|
| Appearance | Brown | Specific Gravity (Water = 1) | 0.79 |
| Odor | NA | Boiling Point | NA |
| Solubility in Water | NA | Vapor Density (Air=1) | NA |
| Physical State | Solid | Vapor Pressure | NA |
| pH | NA | Freezing Point | NA |

10. STABILITY AND REACTIVITY

Conditions contributing to instability: None known.

Incompatibilities: None known.

Hazardous Reactions/Decomposition/Combustion Products: Combustion products may include smoke.

Hazardous Polymerization: Does not occur.

January 1, 2020

11. TOXICOLOGICAL INFORMATION

Carcinogenicity Data: IARC has classified untreated hardwood and hardwood/softwood mix wood dust as a Group I human carcinogen. The wood dust classification is based primarily on IARC's evaluation of increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with occupational exposures to untreated wood dust. Wood dust is not listed as a carcinogen by NTP, ACGIH, or OSHA.

11. ECOLOGICAL INFORMATION

No data available.

12. DISPOSAL CONSIDERATIONS

Disposal Guidance: Dispose of in accordance with local, state and federal regulations. State run hazardous waste programs may be more stringent. Typically this product can be disposed of in approved landfills.

13. TRANSPORT INFORMATION

DOT Hazardous Material Classification: This material is not regulated as a hazardous material by the DOT.

14. REGULATORY INFORMATION

OSHA (29 CFR 1910.1200): This product is regulated under the Hazard Communication Standard. Wood dust, by a product generated from sawing or machining wood and wood products, is considered hazardous and is regulated under the Hazard Communications Standard 29 CFR 1910 1200.

ABBREVIATIONS

| | | | |
|---------------|---|--------------|--|
| OSHA | Occupational Safety and Health Administration | TLV | Threshold Limit Value |
| ACGIH | American Conference of Governmental Industrial Hygienists | STEL | Short-Term Exposure Limit |
| FIFRA | Federal Insecticide, Fungicide and Rodenticide Act | RCRA | Resource Conservation and Recovery Act |
| CERCLA | Comprehensive Environmental Response, Compensation, and Liability Act | NFPA | National Fire Protection Association |
| SARA | Superfund Authorization and Reauthorization Act | NIOSH | National Institute of Occupational Safety and Health |
| PEL | Permissible Exposure Limit | | |

NOTICE & DISCLAIMERS:

Any and all MSDS information is a part of the Public Domain and available to any and all at any time. It is the user's responsibility to provide and post all applicable MSDS information, and to inform all users, employees, customers et al of the hazards of wood dust.

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, this manufacturer makes no guarantee or warranty, expressed or implied, as to the accuracy, reliability, or completeness of the information.

Untreated Wood Products, Inc.

Untreated Wood Products, Inc.