Cover Crop Rollers

Manage high-density cover crops • Increase soil organic matter • Save time and money • Improve soil structure

Make the move to organic farming & reduce the amount of herbicides

in your conventional farming program!



- The Cover Crop Roller mounts to the front of the tractor with a three-point hitch, leaving room for the seeder at the back. This means you can knock down weed-suppressing mats of cover crop, and plant through it all in the same pass! Saving you fuel and time all while building up your soil!
- Can be either mounted three point on tractors or trailed (even horse-drawn)
- Our roller can be built from 3 ft. through 60 ft. making it suitable for use on either small or large farms
- Roller is ground-driven







	101/2' 3pt	8′ 3pt	6′ 3pt	5′ 3pt	4′ 3pt	5' Flipover	4' Flipover	Adapter Plate	8' trailed
SPECIFICATIONS	910	908	906	905	904	905T	904T	901	908TK
Overall Width When Working	130"	100"	76"	63"	52"	84"	72"	46"	133"
Transport Width	130"	100"	76"	63"	52"	84"	72"	46"	133"
Transport Height	60"	60"	60"	60"	60"	29"	29"	46"	43"
Working Height	36"	36"	36"	36"	36"	29"	29"	24"	43"
Length Front to Back	35"	35"	35"	35"	35"	64"	364"	8"	120"
Horse Power Required	75	60	40	30	24	18	16	none	24
Hydraulics Required	none	none	none	none	none	none	none	none	I valve 2 hoses
Weight	1835	1510	1190	1100	850	1150	995	195	1910
Shipping Dimensions	132" x 48" x 36"	102" x 48" x 36"	76" x 48" x 36"	63" x 48" x 36"	52" x 48" x 36"	84" x 48" x 29"	72" x 48" x 29"	52" X 12" x 48"	133" x 48" x 48

Cover Crop Rollers

Manage high-density cover crops • Increase soil organic matter • Save time and money • Improve soil structure

Make the move to organic farming & reduce the amount of herbicides

in your conventional farming program!





- The Cover Crop Roller can be mounted to the front or rear of the tractor. This means you can knock down weed-suppressing mats of cover crop. Saving you fuel and time all while building up your soil!
- Can be either mounted three point on tractors, front end loaders, or trailed (even horse-drawn)
- Our roller can be built from 3' wide to 60' wide making it suitable for use on either small or large farms and deer managed food plots.
- Roller is ground-driven







	60' trailed	40' trailed	30' trailed	20' trailed	15½′ 3pt	Adapter Plate
SPECIFICATIONS	960	940	930T	920T	915	901
Overall Width When Working	60'	40'	354"	244"	190"	46"
Transport Width	159"	159"	190"	130"	190"	46"
Transport Height	108"	108"	128"	120"	60"	24"
Working Height	36'	26' 3"	62"	62"	36"	24"
Length Front to Back in transport	24' (field position)	235"	190"	180"	35"	8"
Horse Power Required	200	150	120	90	90	
Hydraulics Required	3 bank	2 bank	2 bank	2 bank	none	none
Weight	11,164lbs	5,344	7900 lb	6000 lb	2400	195
Shipping Dimensions	8 ft x 48 ft truck space	8ft x 32 ft truck space	8 ft x 25 ft truck space	8 ft x 25 ft truck space	190" x 48" x 36"	52" X 12" x 48"