

GALVANIZED STEEL POST 2-1/2" X 6'

KCS GALVANIZED STEEL POSTS ARE MANUFACTURED FROM STRIP STEEL THAT CONFORMS TO ASTM-A-653. THE STEEL IS COLD ROLLED AND MEETS A MINIMUM YIELD STRENGTH OF 50,000 PSI. THEY ARE ZINCE COATED TO CONFORM TO ASTM B6 AND HAVE A COATING WEIGHT OF 2.10oz SQ/FT (G-210). THERE IS A CONVERSION COATING AND ORGANIC CLEAR COAT APPLIED DURING MANUFACTURING FOR CORROSION RESISTANCE.

OUTSIDE DIAMETER:	<u>2-1/2 INCHES</u>
DECIMAL O.D. EQUIVALENT:	<u>2.375 INCHES</u>
PIPE WALL THICKNESS:	<u>.130 INCHES</u>
WEIGHT:	<u>3.12 LB/FT</u>
MAX BENDING MOMENT:	<u>24405 LB/INCH</u>
CALCULATED LOAD:	<u>339 LBS</u>
LENGTH:	<u>6 FEET</u>

**** KCS GALVANIZED STEEL POSTS 2-1/2" MEET AND/OR EXCEED THE SPECIFICATIONS ABOVE ****