

Your One Source for Cleaning and Maintenance Products

ALL-PURPOSE HIGH-TEMPERATURE

Multi-Purpose, Anti-Spatter Grease

All-Purpose High-Temperature is a multi-purpose grease fortified with special additives, enabling it to withstand the heavy impact and pounding pressures common to heavy equipment.



FEATURES/BENEFITS:

Lubricates	Provides lubrication for a wide variety of parts and equipment	
Stays Put	Lasts longer than many conventional greases, won't pound out	
Extreme Pressure Additive	Excellent load carrying capability with a 65 lb. Timken OK load	
Special Rust and Corrosion Inhibitors	Resists corrosion and the resulting seizing of fittings	
Stable in Most Environments	Resists most acids, weather, dirt, water, steam, and oxidation	

APPLICATIONS:

All-Purpose High-Temperature provides superior protection to lubricate a wide variety of automotive, trucking, industrial, mining, and construction equipment. For use in: automotive repair shops, fabricated metal shops, motorcycle dealer, construction companies, industrial machinery manufacturers, new & used car dealers, electrical contractors, service stations, oil and natural gas drilling, various manufacturing applications, and other industrial processes.

SPECIFICATIONS:

NLGI Grade (ASTM D-217)	2.5
Worked Penetration (ASTM D-217)	245-265
Thickener Type	Clay
Color	Green
Texture	Stringy, adhesive
Base Oil	Naphthenic Oil
Temperature Range	-0 to 400°F
Rust Prevention D-1743 Rating	PASS
Dropping Point D-556	>500°F
4-Ball Weld Load (ASTM D-2596)	400 kgf
Timken OK Load (ASTM D-2509	65 lbs

PACKAGING:

10 cartridge per box (14oz.per cartridge)

Order Code	Product Name	Packing / Unit	Order Units
312101	All-Purpose High-Temperature – Multi-Purpose, Anti-Spatter Grease	Cartridge / box	Per Cartridge



Mobile: 016 4306643 Tel: 07 361 3331