

# FORMULA 14B

Mineral & Hard Water Remover

## DIRECTIONS

### Preparation:

Dilute product with water as follows:

Light to Medium Soils: 16 oz / gallon.

Medium to Heavy Soils: 32 oz/ gallon

### Application for small area surfaces:

Spray area liberally with diluted solution.

Allow product dwell time of 30 seconds to 1 minute. Wipe area and remove solution.

Rinse area, if necessary.

### Application for large area surfaces:

Fill pressure washer, no touch cleaning system, or pump up sprayer with Formula 14B diluted solution. Apply a thin layer to surface and allow a dwell time of at least 30 seconds. Rinse solution. Light abrasion or scrubbing may be required for more difficult stains and rust.

**Warning:** Avoid contact with eyes and skin. Protective eyewear, clothing, and a NIOSH N95 mask or respirator recommended.

**First Aid: Eyes** - Flush with plenty of water for at least 15 min..

**Skin** - Flush with plenty of water.

**Ingestion** - Rinse out mouth. Drink plenty of water, but do not induce vomiting

**Inhalation** - Move to fresh air.

If irritation persists, see a physician immediately.

**FORMULA 14B** works fast to penetrate and lift off hard water, lime, or organic matter, water deposits, stains caused by mold & mildew, even light rust. An excellent acid product for light, medium and even some heavy restroom soils when used in a routine maintenance program, as well as in appropriate initial "shock" cleaning processes.

**FORMULA 14B** is an environmentally and human preferable solution to problems usually solved by harsh acids and chemicals that typically cause damage to skin and respiratory systems.

**Formula 14B can be used on:**

- Ceramic Tile & Grout
- Stainless Steel
- Concrete
- Porcelain
- Metal Fixtures
- Fiberglass

pH:	<1.0
COLOR :	Colorless to light yellow
WATER SOLUBILITY:	Complete
FLASH POINT:	None

Manufactured by:

EARTH LABORATORIES, INC.

866.203.0535

[www.earthlaboratories.com](http://www.earthlaboratories.com)