

Job Name	
Job Location	
P.O.#	
Engineer	
Contractor	
Wholesaler	
CopperPress® Rep	


Description: CopperPress® Small Diameter Bushing Reducer is available in sizes ½” – 2” and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M ½” – 2” copper tubing in the hard-drawn condition and soft copper tubing in sizes ½” to 1¼”.

Features:


- **Visual Indicator Press Ring (VIPR)** – facilitates immediate identification of un-pressed connections
- **Leak Before Press** – in addition to the VIPR, valve incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws
- **Copper Ends** - protect against dezincification and stress corrosion cracking

Operational Parameters: Operating / Test Pressure = 300 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51



Item Number	D1 (in)	D2 (in)	L (in)	A (in)
12530	¾”	½”	2.05	1.24
12540	1”	½”	2.32	1.52
12550	1”	¾”	2.24	1.30
12560	1¼”	½”	2.64	1.83
12570	1¼”	¾”	2.64	1.69



Item Number	D1 (in)	D2 (in)	L (in)	A (in)
12580	1¼"	1"	2.52	1.57
12585	1½"	½"	3.03	2.22
12590	1½"	¾"	3.11	2.17
12600	1½"	1"	2.95	2.01
12610	1½"	1¼"	3.03	1.89
12613	2"	½"	3.66	2.85
12617	2"	¾"	3.74	2.80
12620	2"	1"	3.54	2.60
12630	2"	1¼"	3.58	2.44
12640	2"	1½"	3.70	2.24