



Job Name	
Job Location	
P.O.#	
Engineer	
Contractor	
Wholesaler	
CopperPress® Rep	


Description: CopperPress® Small Diameter Press Tee Female Reducer P x P x FPT is available in sizes ½” – 2” and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M copper tubing in the hard-drawn condition and soft copper tubing in sizes ½” to ¼”.

Features:


- **Visual Indicator Press Ring (VIPR)** – facilitates immediate identification of un-pressed connections
- **Leak Before Press** – in addition to the VIPR, valve incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws
- **Copper Ends** - protect against dezincification and stress corrosion cracking

Operational Parameters: Operating / Test Pressure = 300 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51



Item Number	D1 (in)	D2 (in)	L1 (in)	A1 (in)	L2 (in)	A2 (in)
40000	½”	½” FPT	1.56	0.75	1.44	0.89
40010	¾”	¼” FPT	1.63	0.69	1.34	0.93
40020	¾”	½” FPT	1.79	0.85	1.38	0.83
40030	¾”	¾” FPT	1.79	0.85	1.61	0.98
40040	1”	½” FPT	1.63	0.69	1.71	1.16
40050	1”	¾” FPT	1.79	0.85	1.85	1.22



Item Number	D1 (in)	D2 (in)	L1 (in)	A1 (in)	L2 (in)	A2 (in)
40060	1/4"	1/2" FPT	1.87	0.73	1.77	1.22
40070	1/4"	3/4" FPT	1.99	0.85	1.85	1.22
40080	1/2"	1/2" FPT	2.13	0.67	1.81	1.26
40100	1/2"	3/4" FPT	2.26	0.81	1.97	1.34
40110	2"	1/2" FPT	2.42	0.81	2.13	1.57
40120	2"	3/4" FPT	2.54	0.93	2.32	1.69