



Image Coming Soon

Job Name	
Job Location	
P.O.#	
Engineer	
Contractor	
Wholesaler	
CopperPress® Rep	


Description: CopperPress® XL Tee Female Reducer is available in sizes 2½” – 4” and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M copper tubing in the hard-drawn condition.

Features:

- **Visual Indicator Press Ring (VIPR)** – facilitates immediate identification of un-pressed connections
- **Leak Before Press** – in addition to the VIPR, valve incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws
- **Copper Ends** - protect against dezincification and stress corrosion cracking

Operational Parameters: Operating / Test Pressure = 300 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51



Item Number	D1 (in)	D2 (in)	L1 (in)	A1 (in)	L2 (in)	A2 (in)
42000	2½”	¾” FPT	3.25	1.52	3.50	2.87
42010	2½”	2” FPT	3.25	1.52	3.43	2.48
42020	3”	¾” FPT	3.64	1.63	4.02	3.39
42030	3”	2” FPT	3.64	1.63	3.58	2.64
42040	4”	¾” FPT	4.02	1.61	3.90	3.27
42050	4”	2” FPT	4.02	1.61	3.70	2.76
42060	2½”	¾” FPT	3.25	1.52	3.50	2.87