



|                         |  |
|-------------------------|--|
| <b>Job Name:</b>        |  |
| <b>Job Location:</b>    |  |
| <b>P.O.#:</b>           |  |
| <b>Engineer:</b>        |  |
| <b>Contractor:</b>      |  |
| <b>Wholesaler:</b>      |  |
| <b>CopperPress Rep:</b> |  |

**Description:** CopperPress® Press Pex Adapter is available in sizes 1" – 4" and is made of lead-free dezincification resistant bronze with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M copper tubing in the hard-drawn condition and soft copper tubing in sizes ½" to 1¼".

**Features:**

- **Visual Indicator Press Ring (VIPR)** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H<sub>2</sub>O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the VIPR, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H<sub>2</sub>O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

**Operational Parameters:** Operating / Test Pressure = 300 psi / 600 psi, Temperature Range 0°F - 250°F

**Approvals:** NSF ANSI/CAN 61

| Item # | D1  | L (in) | A (in) | b (in) | D (in) | K (in) | d (in) |
|--------|-----|--------|--------|--------|--------|--------|--------|
| 60000  | 1"  | 2.28   | 1.34   | 0.63   | 4.33   | 3.11   | 0.63   |
| 60010  | 1¼" | 2.28   | 1.14   | 0.63   | 4.53   | 3.50   | 0.63   |
| 60020  | 1½" | 2.60   | 1.14   | 0.63   | 4.92   | 3.86   | 0.63   |
| 60030  | 2"  | 2.76   | 1.14   | 0.63   | 5.91   | 4.76   | 0.75   |
| 60040  | 2½" | 2.83   | 1.10   | 0.69   | 7.09   | 5.51   | 0.75   |
| 60050  | 3"  | 3.35   | 1.34   | 0.81   | 7.48   | 5.98   | 0.75   |
| 60060  | 4"  | 3.74   | 1.34   | 0.89   | 9.06   | 7.52   | 0.75   |

