



Job Name:	
J ob Location:	
P.O.#:	
Engineer:	
Contractor:	
Wholesaler:	
CopperPress Rep:	

Description: CopperPress® Small Diameter Male Street Adapter is available in sizes ½" – 2" and is made of lead-free dezincification resistant bronze with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M ½" – 2" copper tubing in the hard-drawn condition and soft copper tubing in sizes ½" to 1¼".

Features:

- **Visual Indicator Press Ring (VIPR)** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H₂O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the VIPR, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 300 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51

Item Number	D1 (in)	D2 (in)	L (in)
22900	½"	⅜" MPT	1.69
22910	½"	⅜" MPT	1.77
22920	½"	¾" MPT	1.93
22930	¾"	½" MPT	1.93
22940	¾"	¾" MPT	1.97
22950	1"	¾" MPT	1.97
22960	1"	1" MPT	2.13
22970	1¼"	1¼" MPT	2.48
22980	1½"	1½" MPT	2.87
22990	2"	2" MPT	3.19

