



<b>Job Name:</b>	
<b>Job Location:</b>	
<b>P.O.#:</b>	
<b>Engineer:</b>	
<b>Contractor:</b>	
<b>Wholesaler:</b>	
<b>CopperPress Rep:</b>	

**Description:** CopperPress® Small Diameter Press 90° Elbow is available in sizes 1/2" – 2" and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M 1/2" – 2" copper tubing in the hard-drawn condition and soft copper tubing in sizes 1/2" to 1 1/4".

**Features:**

- **Visual Indicator Press Ring (VIPR)** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H<sub>2</sub>O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the VIPR, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H<sub>2</sub>O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

**Operational Parameters:** Operating / Test Pressure = 300 psi / 600 psi, Temperature Range 0°F - 250°F

**Approvals:** NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51

Item Number	Size D1 (in)	L (in)	A (in)
11230	1/2"	1.56	0.75
11240	3/4"	1.97	1.02
11250	1"	2.24	1.30
11260	1 1/4"	2.64	1.50
11270	1 1/2"	3.23	1.77
11280	2"	3.98	2.36

