

Submittal Sheet

Elbow P x MPT



Job Name:	
Job Location:	
P.O.#:	
Engineer:	
Contractor:	
Wholesaler:	
CopperPress Rep:	

Description: CopperPress[®] Small Diameter Press 90° Elbow P x MPT is available in sizes ½" – 2" and is made of lead-free dezincification resistant bronze with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M copper tubing in the hard-drawn condition and soft copper tubing in sizes 1/2" to 11/4".

Features:

- Visual Indicator Press Ring (VIPR) facilitates immediate identification of unpressed connections as well as application – green = EPDM (H₂O), yellow = HNBR (gas)
- Leak Before Press in addition to the VIPR, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- Permanent Application Marking imprinted on fitting body for quick H₂O or gas application identification
- Lead Free Construction fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 300 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51

Item #	Size D1	Size D2	L1 (in)	A (in)	L2 (in)
47990	1/2"	1⁄₂" MPT	1.56	0.75	1.87
48000	1/2"	3/4" MPT	2.01	1.20	2.01
48010	3/4"	1/2" MPT	2.15	1.20	2.15
48012	3/,"	3/4" MPT	2.03	1.09	2.11
48015	1"	1" MPT	2.24	1.28	2.76
48020	11/4"	11/4" MPT	2.64	1.50	2.64
48030	1½"	11/2" MPT	3.23	1.77	3.23
48040	2"	2" MPT	4.25	2.64	4.25





