



<b>Job Name:</b>	
<b>Job Location:</b>	
<b>P.O.#:</b>	
<b>Engineer:</b>	
<b>Contractor:</b>	
<b>Wholesaler:</b>	
<b>CopperPress Rep:</b>	

**Description:** CopperPress® Small Diameter Press Coupling with Stop is available in sizes ½" – 2" and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M ½" – 2" copper tubing in the hard-drawn condition and soft copper tubing in sizes ½" to 1¼".

**Features:**

- **Visual Indicator Press Ring (VIPR)** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H<sub>2</sub>O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the VIPR, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H<sub>2</sub>O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

**Operational Parameters:** Operating / Test Pressure = 300 psi / 600 psi, Temperature Range 0°F - 250°F

**Approvals:** NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51

Item Number	Size D1 (in)	L (in)	A (in)
12230	½"	1.61	0.12
12240	¾"	2.05	0.16
12250	1"	2.05	0.16
12260	1¼"	2.44	0.16
12270	1½"	3.03	0.16
12280	2"	3.35	0.16

