



Job Name:	
Job Location:	
P.O.#:	
Engineer:	
Contractor:	
Wholesaler:	
CopperPress Rep:	

Description: CopperPress® Small Diameter Press Female Adapter is available in sizes ½" – 2" and is made of lead-free dezincification resistant bronze with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M ½" – 2" copper tubing in the hard-drawn condition and soft copper tubing in sizes ½" to 1¼".

Features:

- **Visual Indicator Press Ring (VIPR)** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H₂O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the VIPR, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 300 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51

Item Number	D1 (in)	D2 (in)	L (in)	A (in)
22600	½"	⅜" FPT	1.42	0.35
22610	½"	½" FPT	1.61	0.28
22620	½"	¾" FPT	1.65	0.22
22630	¾"	½" FPT	1.61	0.18
22640	¾"	¾" FPT	1.81	0.22
22650	1"	½" FPT	2.09	0.57
22660	1"	¾" FPT	1.73	0.14
22670	1"	1" FPT	1.89	0.20
22680	1"	1¼" FPT	2.13	0.31
22690	1¼"	1" FPT	2.09	0.16
22700	1¼"	1¼" FPT	2.20	0.24
22710	1¼"	1½" FPT	2.20	0.22
22720	1½"	1¼" FPT	2.48	0.24
22730	1½"	1½" FPT	2.52	0.22
22740	2"	2" FPT	2.83	0.22

