



Job Name:	
Job Location:	
P.O.#:	
Engineer:	
Contractor:	
Wholesaler:	
CopperPress Rep:	

Description: CopperPress® Small Diameter Press Male Adapter is available in sizes ½" – 2" and is made of lead-free dezincification resistant bronze with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M ½" – 2" copper tubing in the hard-drawn condition and soft copper tubing in sizes ½" to 1¼".

Features:

- **Visual Indicator Press Ring (VIPR)** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H₂O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the VIPR, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 300 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51

Item Number	D1 (in)	D2 (in)	L (in)	A (in)
23250	½"	¾" MPT	1.65	0.85
23260	½"	½" MPT	1.69	0.89
23270	½"	¾" MPT	1.77	0.96
23280	¾"	½" MPT	2.05	1.10
23290	¾"	¾" MPT	1.89	0.94
23300	¾"	1" MPT	2.05	1.10
23310	1"	½" MPT	2.13	1.18
23320	1"	¾" MPT	1.93	0.98
23330	1"	1" MPT	1.93	1.22
23340	1"	1¼" MPT	2.09	1.14
23350	1¼"	1" MPT	2.20	1.06
23360	1¼"	1¼" MPT	2.20	1.06
23370	1¼"	1 ½" MPT	2.28	1.14
23380	1 ½"	1¼" MPT	2.70	1.24
23390	1 ½"	1 ½" MPT	2.64	1.18
23400	1 ½"	2" MPT	2.64	1.18
23410	2"	1 ½" MPT	2.83	1.22
23420	2"	2" MPT	2.80	1.46

