



Job Name	
Job Location	
P.O.#	
Engineer	
Contractor	
Wholesaler	
CopperPress® Rep	


Description: CopperPress® Small Diameter Press Unequal Tee is available in sizes ½” – 2” and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M ½” – 2” copper tubing in the hard-drawn condition and soft copper tubing in sizes ½” to ¼”.

Features:

- **Color ID Press Band** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H₂O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the press band, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 200 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51



Item Number	D1 (in)	D2 (in)	D3 (in)	L1 (in)	L2 (in)	L3 (in)	A1 (in)	A2 (in)	A3 (in)
14120	½”	½”	¾”	1.71	0.91	1.71	0.91	1.54	0.59
14130	½”	½”	1”	1.73	0.79	1.71	0.91	1.71	0.91
14150	¾”	½”	½”	1.63	0.69	1.75	0.94	1.40	0.59
14160	¾”	½”	¾”	1.79	0.85	1.87	1.06	1.57	0.63
14170	¾”	¾”	½”	1.63	0.69	1.63	0.69	1.38	0.57
14180	¾”	¾”	1”	1.91	0.96	1.91	0.96	1.97	1.02