



Job Name	
Job Location	
P.O.#	
Engineer	
Contractor	
Wholesaler	
CopperPress® Rep	


Description: CopperPress® XL Press Unequal Tee is available in sizes 2½” – 4” and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M copper tubing in the hard-drawn condition.

Features:

- **Color ID Press Band** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H₂O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the press band, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 200 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51



Item Number	D1 (in)	D2 (in)	D3 (in)	L1 (in)	A1 (in)	L2 (in)	A2 (in)	L3 (in)	A3 (in)
24110	2½”	¾”	2½”	3.56	1.83	4.17	3.23	3.66	1.93
24120	2½”	1”	2½”	3.56	1.83	4.19	3.25	3.60	1.87
24130	2½”	1¼”	2½”	3.56	1.83	4.35	3.21	3.60	1.87
24140	2½”	1½”	2½”	3.56	1.83	4.61	3.15	3.60	1.87
24150	2½”	2”	¾”	3.25	1.52	3.72	2.11	3.74	2.80
24160	2½”	2”	1”	3.25	1.52	3.72	2.11	3.54	2.60