



Job Name	
Job Location	
P.O.#	
Engineer	
Contractor	
Wholesaler	
CopperPress[®] Rep	


Description: CopperPress[®] Small Diameter Press Dielectric Female Union is available in sizes ½” – 2” and is made of carbon steel and lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress[®] fittings are designed to be used with ASTM B88 Type K, L and M ½” – 2” copper tubing in the hard-drawn condition and soft copper tubing in sizes ½” to 1¼”.

Features:

- **Color ID Press Band** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H2O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the press band, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H2O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 200 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51



Item Number	D1 (in)	D2 (in)	L (in)	A (in)
37000	½”	½” FPT	2.64	1.32
37010	¾”	¾” FPT	3.07	1.54
37020	1”	1” FPT	2.76	1.14
37030	1¼”	1¼” FPT	3.03	1.10
37040	1½”	1½” FPT	3.46	1.22
37050	2”	2” FPT	3.78	1.22