



Job Name	
Job Location	
P.O.#	
Engineer	
Contractor	
Wholesaler	
CopperPress® Rep	


Description: CopperPress® XL Press Bushing Reducer is available in sizes 2½” – 4” and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M ½” – 2” copper tubing in the hard-drawn condition.

Features:

- **Color ID Press Band** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H₂O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the press band, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 200 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51



Item Number	D1 (in)	D2 (in)	L (in)	A (in)
22400	2½”	1”	4.25	3.31
22410	2½”	1¼”	4.06	2.91
22420	2½”	1½”	4.29	2.83
22430	2½”	2”	4.25	2.64
22440	3”	1¼”	4.53	3.39
22450	3”	1½”	4.92	3.46
22460	3”	2”	4.80	3.19
22470	3”	2½”	4.53	2.80
22480	4”	2”	6.18	4.57
22490	4”	2½”	5.79	4.06
22500	4”	3”	5.71	3.70

Customer Service (877) 890-2283
www.copperpress.com

Supply Source Products reserves the right to change any portion of the information shown on this submittal without obligation to change CopperPress® products previously or subsequently sold. See www.copperpress.com for most current information.

