



Job Name	
Job Location	
P.O.#	
Engineer	
Contractor	
Wholesaler	
CopperPress® Rep	


Description: CopperPress® Small Diameter Female Street Adapter is available in sizes ½” – 2” and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M ½” – 2” copper tubing in the hard-drawn condition and soft copper tubing in sizes ½” to 1¼”.

Features:

- **Color ID Press Band** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H2O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the press band, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H2O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 200 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51



Item Number	D1 (in)	D2 (in)	L (in)	A (in)
32000	½”	⅜” FPT	1.57	1.10
32010	½”	½” FPT	1.73	1.18
32020	½”	¾” FPT	1.93	1.30
32030	¾”	½” FPT	1.73	1.18
32040	¾”	¾” FPT	1.93	1.30
32050	1”	½” FPT	1.81	1.26
32060	1”	¾” FPT	1.93	1.30
32070	1”	1” FPT	1.99	1.28
32080	1¼”	1¼” FPT	2.32	1.54
32090	1½”	1½” FPT	2.58	1.75
32100	2”	2” FPT	3.07	2.09