



|                         |  |
|-------------------------|--|
| <b>Job Name</b>         |  |
| <b>Job Location</b>     |  |
| <b>P.O.#</b>            |  |
| <b>Engineer</b>         |  |
| <b>Contractor</b>       |  |
| <b>Wholesaler</b>       |  |
| <b>CopperPress® Rep</b> |  |


**Description:** CopperPress® Small Diameter Press Coupling with Stop is available in sizes ½" – 2" and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M ½" – 2" copper tubing in the hard-drawn condition and soft copper tubing in sizes ½" to 1¼".

#### Features:

- **Color ID Press Band** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H<sub>2</sub>O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the press band, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H<sub>2</sub>O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

**Operational Parameters:** Operating / Test Pressure = 200 psi / 600 psi, Temperature Range 0°F - 250°F

**Approvals:** NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51



| Item Number | D1 (in) | D2 (in) | L1 (in) |
|-------------|---------|---------|---------|
| 12230       | ½"      | 1.77    | 0.16    |
| 12240       | ¾"      | 2.05    | 0.16    |
| 12250       | 1"      | 2.05    | 0.16    |
| 12260       | 1¼"     | 2.44    | 0.16    |
| 12270       | 1½"     | 3.19    | 0.28    |
| 12280       | 2"      | 3.50    | 0.28    |