



Job Name	
Job Location	
P.O.#	
Engineer	
Contractor	
Wholesaler	
CopperPress® Rep	



Description: CopperPress® Press Adapter Flange is available in sizes 1" – 4" and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M ½" – 2" copper tubing in the hard-drawn condition and soft copper tubing in sizes ½" to 1¼".

Features:

- **Color ID Press Band** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H₂O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the press band, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 200 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51



Item Number	D1 (in)	L (in)	A (in)	b (in)	D (in)	K (in)	d (in)
60000	1"	2.28	1.34	0.63	4.33	3.11	0.63
60010	1¼"	2.28	1.14	0.63	4.53	3.50	0.63
60020	1½"	2.60	1.14	0.63	4.92	3.86	0.63
60030	2"	2.76	1.14	0.63	5.91	4.76	0.75
60040	2½"	2.83	1.10	0.69	7.09	5.51	0.75
60050	3"	3.35	1.34	0.81	7.48	5.98	0.75
60060	4"	3.74	1.34	0.89	9.06	7.52	0.75

Customer Service (877) 890-2283
www.copperpress.com

Supply Source Products reserves the right to change any portion of the information shown on this submittal without obligation to change CopperPress® products previously or subsequently sold. See www.copperpress.com for most current information.

