



Job Name	
Job Location	
P.O.#	
Engineer	
Contractor	
Wholesaler	
CopperPress® Rep	


Description: CopperPress® Small Diameter Press Cap is available in sizes ½" – 2" and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. vFittings are designed to be used with ASTM B88 Type K, L and M copper tubing in the hard-drawn condition and soft copper tubing in sizes ½" to 1¼".

Features:

- **Color ID Press Band** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H₂O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the press band, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 200 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51



Item Number	D1 (in)	L1 (in)	A (in)
13110	½"	0.94	0.14
13120	¾"	1.06	0.12
13140	1"	1.06	0.12
13150	1¼"	1.26	0.12
13160	1½"	1.69	0.24
13170	2"	1.85	0.24