



Job Name:	
Job Location:	
P.O.#:	
Engineer:	
Contractor:	
Wholesaler:	
CopperPress Rep:	

Description: CopperPress® XL Press Coupling with Stop is available in sizes 2½" – 4" and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. Fittings are designed to be used with ASTM B88 Type K, L and M copper tubing in the hard-drawn condition.

Features:

- **Visual Indicator Press Ring (VIPR)** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H₂O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the VIPR, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 300 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51

Item Number	Size D1 (in)	L (in)	A (in)
22230	2 ½"	3.86	0.39
22240	3"	4.37	0.35
22250	4"	5.20	0.39

