



Job Name:	
Job Location:	
P.O.#:	
Engineer:	
Contractor:	
Wholesaler:	
CopperPress Rep:	

Description: CopperPress® XL Tee Female Reducer is available in sizes 2½" – 4" and is made of lead-free dezincification resistant copper with an EPDM or HNBR o-ring. CopperPress® fittings are designed to be used with ASTM B88 Type K, L and M copper tubing in the hard-drawn condition.

Features:

- **Visual Indicator Press Ring (VIPR)** – facilitates immediate identification of un-pressed connections as well as application – green = EPDM (H₂O), yellow = HNBR (gas)
- **Leak Before Press** – in addition to the VIPR, fitting incorporates four path LBP technology, guaranteeing a visual indication if not pressed
- **Permanent Application Marking** – imprinted on fitting body for quick H₂O or gas application identification
- **Lead Free Construction** – fully compliant with current lead-free laws

Operational Parameters: Operating / Test Pressure = 300 psi / 600 psi, Temperature Range 0°F - 250°F

Approvals: NSF ANSI/CAN 61, UPC, cUPC, IPC, IAPMO PS-117, ICC-ES-PMG, ASME B16.51

Item #	Size D1	Size D2	L1 (in)	A1 (in)	L2 (in)	A2 (in)
42000	2½"	¾" FPT	3.25	1.52	3.50	2.87
42010	2½"	2" FPT	3.25	1.52	3.43	2.48
42030	3"	¾" FPT	3.64	1.63	4.02	3.39
42040	3"	2" FPT	3.64	1.63	3.58	2.64
42050	4"	¾" FPT	4.02	1.61	3.90	3.27
42060	4"	2" FPT	4.02	1.61	3.70	2.76

