

DEER CREEK

August 2015


The Innovation of Transforming Wastewater Treatment Plants into Water Resource Recovery Facilities





ANAEROBIC DIGESTION - WASTEWATER TREATMENT

Over the next 10 years, wastewater treatment plants (WWTP) will undergo profound — changes







Following a groundbreaking ceremony on March 26, 2014, Stanford is moving forward on the construction of the William and Cloy Codiga Resource Recovery Center, "CR2C" for short, whose main purpose will be to testbed and demonstrate scalability of promising wastewater treatment technologies and essentially serve as an innovation accelerator. One of the first key projects will be a test of resource recovery technology at pilot-scale, extracting clean water, nutrients, energy and chemical feedstocks from wastewater




The Value of the Resource

Resource	Per m³	US \$ per m³	
Organic Soil Conditioner (kg)	0.10	0.03	
Methane (m³)	0.14	0.07	
Nitrogen (kg)	0.05	0.07	
Phosphorus (kg)	0.01	0.01	
Water (1 m³)	1.00	0.33	1

Source: Willy Verstraete (2008)

Process Flow Chart





Facility of the future







Gas Cleaning Technology



uasar has collaborated with Air Products to develop proprietary gas cleaning technology.

- Now biogas can be affordably upgraded to biomethane exceeding pipeline quality.
- Ohio organic residuals represent the equivalent of 1,000,000,000 gallons of renewable fuel annually.









© Copyright quasar energy group 2013



Chevy CNG Vehicle




How Quickly did the City benefit? quasa



Monthly Electric Bill

City of Wooster (Ohio)






Do you really see the savings?


August 2013 Invoice

August 2014 Invoice





INPUTS



TYPES OF ORGANIC RESIDUALS:

- Food Processing Residuals
- Manure
- Energy Crops & Spent Grains
- Biobased Oils & Lubricants
- FOG (fats, oils & grease)
- Waste Water Treatment Sludge
- Personal Care Products

- Ethanol and Biodiesel processing residuals
- Dissolved Air Flotation (DAF)
- · Expired, damaged or off-spec consumer goods
- Packaged Organics (depackaging technology)
- Crop Residuals
- Glycerin & Stillage
- Whey
- Sugar Water


11



Food Waste Has Three (3) Times the Methane Production Potential As Biosolids

- Cattle Manure = 25m³ gas / ton
- Biosolids = 120m³ gas / ton
- Food Waste = 376m³ gas / ton











The Cleveland Indians



- The Cleveland Indians have cut the amount of waste going to the landfill in half over 4 years.
- In 2012, the organization sent approximately 60 tons of food waste to a compost facility.
- They will be able to recycle 80 to 100 tons of food waste with macerating technology and AD.

© Copyright quasar energy group 2013

15



ANAEROBIC DIGESTION





SOLUTIONS

- The Cleveland Indians have cut the amount of waste going to the landfill in half over 4 years
- In 2012, the organization sent approximately 60 tons of food waste to a compost facility
- Going forward, it is estimated that they will be able to recycle 80 to 100 tons of food waste through quasar's more efficient waste management and transportation system and InSinkErator's macerating technology

© Copyright guasar energy group 2013





turning food scraps into renewable energy & nutrient-rich fertilizer



Solutions - Food waste management










Microbial Fuel Cell






12 Tubular MFC Modules

















TN1: the right microbe to do the job

- Can use VFAs as food.
- Makes LOTS of hydrogen and PHA.
- Can grow aerobically and anaerobically.







PHA bottle biodegradation over a period of 2 months.




Mike, I would like to introduce you to Mr Kent Shields, CEO, E3 Clean technologies. Dr Botte, is a professor at OU, Athens. We got in touch with them, while we were looking to solve the problem of high concentration Ammonia water.

E3 clean technologies uses electrolysis of Ammonia water to produce hydrogen gas.

"Water will be the coal of the future confidence in 1874 Jules Verne

















Process overview for 50,000 GPD digestate





5





Samples from processing dairy manure digestate









California Drought: Orange County expands 'toilet to tap' water recycling

The process works by re-routing a proportion of the 1.3 billion gallons of waste water generated in Southern California each day into a three-step treatment. The first is microfiltration of the treated waste water to remove solids, oils and bacteria, before the resulting liquid goes through reverse osmosis, pushing it through a fine plastic membrane that filters out viruses and pharmaceuticals. The water is then treated with UV light to remove any remaining organic compounds, before joining the main groundwater supply, which must pass strict quality controls to meet legal standards, and distribution to households.
















Description	Units	Design	Actual
_		Value –	Feed
		Feed	
Na	mg/l	59	62.3
Ca	mg/l	486.4	521.1
$\mathbf{M}\mathbf{g}$	mg/l	216.5	268.3
\mathbf{K}	mg/l	9.8	16.7
Cl	mg/l	18	20.5
HCO_3	mg/l	0	
SO_4	mg/l	2379.5	2481.5
NO_3	mg/l	5	
Acidity	mg/l	256.7	233
Al	mg/l	23.2	17.5
\mathbf{F}	mg/l	0.2	0.1
Fe	mg/l	13.1	20
Mn	mg/l	9.8	9.4
SiO ₂	mg/l	10	
SS	mg/l	101	62.9
Temp.	$^{\circ}\mathbf{C}$	20	
\mathbf{pH}		2.8	5.8
TDS	mg/l	3220.5	3727







667.37 FT²





Dunaliella salina algae



AND GLYCEROL FEED ON BRINE







Management Team

Paul Horst (CEO). Jim Fahrner (CFO)

- Founded industrial computer company, 9x cash over cash exit in 3 years, later spun off as NASDAQ company
- Grew alternative energy subsidiary of DTE Energy to over \$40M

Geoff Horst (CSO), Robert Levine (CTO)

- Developed Algal's patent-pending treatment process
- PhD candidates in biology and chemical engineering

Mike Maringer, James Bleyer (operations, engineering)

- Managed Campbell Soup's largest wastewater treatment million gallons per day), highest certification
- Designed and built bio-fuel plants

Notable Advisors: Joh Kang, Walter Weber

- PhD, VP & Director of water at Tetra Tech
- PhD, Professor Emeritus, U. Michigan

Engineering Partners

- Alan Environmental John Baker
- Tetra Tech







plant (10







42



Algal Scientific's Hypertrophic™ process produces <u>Valuable biomass</u> from <u>Industrial byproducts</u>








Bench-top performance – Brewery process water

	Removal efficiency after:		
Parameter	1 day	3 days	8 days
COD	68%	83%	87%
TN	94%	95%	
TSS	85%		
BOD	73%	91%	95%


A) Untreated wastewater; B) Micro-organisms growing on wastewater; C) Centrifuged micro-organism pellet and supernatant for effluent.













DETROIT FREE PRESS

TomotWalsh: 'Survivability is key' for start-up animal feed maker





OALGAMUNE






http://www.forbes.com/sites/michae lkanellos/2015/04/07/can-algaehelp-the-meat-industry-cut-backon-antibiotics/



NUTRINSIC

We work with food and beverage processors to recover nutrients from their by products.





THANK YOU WASTEWATER **OPERATORS FROM** MIKE MARINGER

TEAMWORK

coming together is a beginning keeping together is progress working together is success

Henry Ford