

Technical Specification

Model: **DS-250K-CSS**

Powered by CUMMINS



Applicable Standards

ISO 8528-5:2018
GB/T2820.5-2009
CE

General Information		Prime power	Standby power
Rated Power (kVA)		284	313
Power Rating (kW)		227	250
Frequency (Hz)		60	
Engine Model		6LTAA9.5-G3	
Engine Speed (RPM)		1800	
Phase		3	
PF		0.8	
Control System		Digital	
Rated voltage (V)		120/208 (According to customer requirements)	
Fuel tank capacity operating time		≥ 8h @ 75% load	
Fuel Consumption (L/h)	110% load	72	
	100% load	65	
	75% load	49	
	50% load	33	

Environmental Conditions


Ambient temperature: +5°C~+40°C
Altitude: ≤1000m
Remark: If your conditions are different from the above, please contact our sales.

Factory Inspection

Complete design and quality inspection
0%, 25%, 50%, 75%, 100%, 110% load test.
Function test.
Protection test

Painting Process

DS Power has the most advanced automatic spraying / powder coating production line, and is equipped with various sandblasting equipment to ensure higher quality.
Canopy painting: Henkel pretreatment process and world famous brand AkzoNobel powder.
Base Frame painting: Sandblasting process and AkzoNobel powder



Dimension and Weight

Model	DS-250K-CSO Open type	DS-250K-CSS Silent type
Length (L) mm	2890	3360
Width (W) mm	1070	1190
Height (H) mm	1780	2020
Dry weight (kg)	1900	3200
Tank capacity (L)	454	600
The loading capacity (40'HC)	8 units	3 units

Note: Specifications and illustrations are subject to revision without notice.



Technical Specification

Engine Specifications

Engine model & manufacturer		6LTAA9.5-G3 (CUMMINS)
Emission Certification		-----
Number of cylinders		6
Cylinder arrangement		In line
Cycle		Four stroke
Aspiration		Turbocharged
Bore x Stroke		116.5x 148 mm
Displacement		9.5 L
Compression ration		16.5: 1
Prime power /speed		265 kW /1800 rpm
Standby power /speed		290 kW /1800 rpm
Speed governor		Electronic
Cooling system		Forced Water Cooling Cycle
Frequency droop		≤5%
Total lubrication system capacity		32.4 L
Coolant capacity		11.1 L
Fuel consumption	100% load	221 g/kWh @1800 rpm
Starter motor		DC 24V
Charge alternator		DC 24V
<ul style="list-style-type: none">◆ Heavy duty diesel engine◆ Anti-vibration mount◆ Replaceable fuel filter, oil filter & air filter◆ Cooling radiator and fan		<ul style="list-style-type: none">◆ Starter battery (with lead acid) including rack and cables◆ Flexible fuel connection hoses◆ Exhaust silencer and bellows◆ Operation manuals and circuit diagram documents

Alternator Specifications

Alternator	UCDI.274K (STAMFORD)
Number of phase	3
Power factor (Cos Phi)	0.8
Poles	4
Insulation type	H class
Winding Pitch	2/3
IP rating	IP23
Bearing	Single bearing
Voltage regulator	A.V.R
Coupling	Flexible disc

Technical Specification

Control Panel

DSE7320MKII

Auto Mains (Utility) Control Module



Key benefits

- 6 Active DC Output
- 4 analog inputs/digital inputs
- 8-way custom digital input
- All expansion modules can be connected
- Can support 0-10V or 4-20mA oil pressure sensor
- With hierarchical loading function
- Support EFI and non-EFI engines
- 3 maintenance alarms can be set
- Engine speed protection
- Engine warm-up
- Multiple start-stop cycles can be preset

Key features

- Built-in PLC logic programming
- 5 menu navigation keys
- Generator voltage detection
- mains voltage detection
- Generator/load power detection (kW, kVA, kVAR, pf)
- Generator overload protection (kW)
- Generator/load current monitoring and protection
- Power saving mode
- With manual closing and opening functions
- Fuel and start-up output can be flexibly defined when used in EFI engines
- Real-time clock
- Fuel pump control function
- Engine Start Rapid & Stop Rapid
- Battery voltage monitoring
- Start the unit when the battery voltage is low
- Custom remote start signal
- Two sets of protected winters can be preset
- Three types of alarm levels can be set: ordinary alarm, electrical trip and shutdown
- LCD and LED alarm indication
- 100 event records
- Optional low temperature version (-40°C)

Options

Engine	Alternator	Fuel System	Generating Set
<ul style="list-style-type: none"> <input type="checkbox"/> Water Jacket Preheater <input type="checkbox"/> Oil Preheater <input type="checkbox"/> Oil manual pump 	<ul style="list-style-type: none"> <input type="checkbox"/> PMG excitation <input type="checkbox"/> Space heater <input type="checkbox"/> Winding temperature measuring 	<ul style="list-style-type: none"> <input type="checkbox"/> 12 / 24 hour base tank <input type="checkbox"/> Bunded fuel tank <input type="checkbox"/> External fuel tank <input type="checkbox"/> Automatic fuel feeding <input type="checkbox"/> Switch between external tank and base tank (three-way valve) 	<ul style="list-style-type: none"> <input type="checkbox"/> Deepsea, ComAp, Smartgen etc. controller <input type="checkbox"/> Trailer <input type="checkbox"/> Tools with the machine

DS SERVICIOS MULTIPLES, SRL.
Calle Sofia Montaña #5, Santa martha, La Venta, SDO.
TEL: (809) 937- 1701,
Email: gerencia@plantasgrandes.com
www.plantasgrandes.com