

TURF




NOTES:


- 1. DESIGN FLOW RATE: 4500 GPM (MAX.)
- Ū OPERATING PRESSURE: 150 PSI (MAX.)

CARTRIDGE: 42″ MIN. CLEARANCE REQUIRED FOR CARTRIDGE REPLACEMENT.






PLAN VIEW



LEFT END VIEW



Ä	>		₩		-	Ž	ž		韻	
REVISION	CARIRIUGE 40 IU 42 PER CARI. IN SEAL		ADDED 1/2' WELD TABS		Translation Giornia, 1997.	모	THE DRAWING IS NOT .	WILE THATCHER IN THE STRING TO THE INTERESTS O	HE INFORMATION AND IS THE PE	
BΥ	יוע		DTO			DNEY \	- H C	MUST NO	F F F F F F F F F F F F F F F F F F F	
BY DATE	6-04		10-12		PIED					
	LOCATION:		DTD 10-12 DRAWING ND: 9080110009	1-19-2001		JMW	DRAWN BY	USED DN	CUSTIDICA	
SYSTEM MES CENTERFEED				VUKEENT IL I			MT010_0/	POWIER NAMEDENT SYSTEMS OF REVERSIBLE, CALIFORNIA	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
SEET] OF]		REV. B		ードス	ו ו			`	₹	