



Deep Bed Sand Media Filters

Removal of Solids
Down to 15 Microns

Yardney Deep Bed Sand Media filters are designed for the most challenging dirty water conditions with a high performance solution for water filtration down to 15 microns. These durable carbon steel filters utilize a 36" vertical side shell depth for removal of organic and inorganic suspended solids for filtering large volumes of water with very little pressure drop and a long-term value. All Yardney industrial media filters utilize our simple backwash system for ease of operation and consistent water quality. The Yardney automatically controlled filter systems operate for extended periods of time prior to a short backwash cycle.



Applications

- Removal of organic and/or inorganic suspended solids down to 15 microns
- 100 psi standard operating pressure (high pressure systems available)
- Storm water runoff, industrial process water, incoming plant water, waste water clean-up, industrial water for plant reuse
- Flow ranges from 11 gpm

Advantages

- State of the art fabrication provides added strength under pressure and long system life
- ASME code shaped head construction for durability and safety
- Stainless steel wedgewire underdrain
 - Ensures structural integrity in the harshest conditions
 - Hydraulically balanced to increase effectiveness of backwash while reducing flush frequency and waste of water
 - High strength stainless steel wedgewire will withstand a collapse pressure in excess of 600 psi
- Standard carbon steel products, 3/16" thick material
- Backwash automatically initiated by elapsed time or pressure differential
- Yardney easy-entry lid closure with weld tabs for operator safety
- Available in welded carbon steel or stainless steel
- 3M Scotchkote® 134 fusion bonded epoxy lining on interior surfaces
- Made in USA

Industrial, Commercial & Municipal

Deep Bed Sand Media Filters

Specifications

SPECIFICATIONS INDUSTRIAL DEEP BED SAND MEDIA FILTERS													
Model	Number of Tanks in System	Standard Flow Range				Filtration Surface Area (total sq ft)	Backwash Flow Rate (per tank)		Media Requirements (cubic feet)		Maximum Pressure	Inlet/Outlet Pipe Size	Backwash Line Pipe Size
		Minimum		Maximum			gpm	m³/hr	Gravel 1/2" - 3/4"	Media			
		gpm	m³/hr	gpm	m³/hr								
IL-1436-1A	1	11	3	16	4	1.07	16	4	1	3	100 psi	2"	2"
IL-1836-1A	1	18	4	26	6	1.75	26	6	1	5	100 psi	2"	2"
IL-1436-2A	2	21	5	32	7	2.14	16	4	1	5	100 psi	2"	2"
IL-2436-1A	1	32	7	47	11	3.15	47	11	2	8	100 psi	2"	2"
IL-1436-3A	3	32	7	48	11	3.21	16	4	1	8	100 psi	2"	2"
IL-1836-2A	2	35	8	53	12	3.50	26	6	2	9	100 psi	3"	2"
IL-3036-1A	1	49	11	74	17	4.91	74	17	3	12	100 psi	3"	3"
IL-1836-3A	3	53	12	79	18	5.25	26	6	3	14	100 psi	3"	2"
IL-2436-2A	2	63	14	95	22	6.30	47	11	3	15	100 psi	3"	2"
IL-3636-1A	1	71	16	107	24	7.10	107	24	4	17	100 psi	3"	3"
IL-2436-3A	3	95	22	142	32	9.45	47	11	5	23	100 psi	3"	2"
IL-3036-2A	2	98	22	147	33	9.82	74	17	5	24	100 psi	4"	2"
IL-4836-1A	1	126	29	189	43	12.60	189	43	7	34	100 psi	4"	4"
IL-3636-2A	2	142	32	213	48	14.20	107	24	8	34	100 psi	4"	4"
IL-3036-3A	3	147	33	221	50	14.73	74	17	8	36	100 psi	4"	2"
IL-5436-1A	1	159	36	238	54	15.90	239	54	10	38	100 psi	4"	4"
IL-3636-3A	3	213	48	320	73	21.30	107	24	12	51	100 psi	4"	4"
IL-4836-2A	2	252	57	378	86	25.20	189	43	14	67	100 psi	6"	4"
IL-5436-2A	2	318	72	476	108	31.80	239	54	19	77	100 psi	6"	4"
IL-4836-3A	3	378	86	567	129	37.80	189	43	21	101	100 psi	6"	4"
IL-5436-3A	3	477	108	714	162	47.70	239	54	29	115	100 psi	6"	4"
IL-4836-4A	4	504	115	756	172	50.40	189	43	28	134	100 psi	8"	4"
IL-4836-5A	5	630	143	945	215	63.00	189	43	35	168	100 psi	10"	4"
IL-5436-4A	4	636	145	952	216	63.60	239	54	38	154	100 psi	8"	4"
IL-4836-6A	6	756	172	1134	258	75.60	189	43	42	201	100 psi	10"	4"
IL-5436-5A	5	795	181	1190	270	79.50	239	54	48	192	100 psi	10"	4"
IL-5436-6A	6	954	217	1428	325	95.40	239	54	57	231	100 psi	10"	4"

Other models and sizes are available.

Standard product includes:

- Completely assembled for easy installation
- Skid mounted tanks
- Yardney easy-entry lid closure with side manway
- Valves
- Inlet/outlet and backwash manifolds
- Controller, solenoids, electrical wire, tubing
- Removable underdrain
- 3M Scotchkote® 134 fusion bonded epoxy lining on interior surfaces

Available options:

- ASME code
- High pressure
- Solar package
- PLC controller
- Custom filter station layout piping
- Air scour



Made in USA

Phone: 951.656.6716
Toll-Free: 800.854.4788
Fax: 951.656.3867
info@yardneyfilters.com



www.yardneyfilters.com