

NL329 - EN857 2SC DOUBLE WIRE HYDRAULIC HOSE



NL329 is a standard double wire hose used in general industrial applications. This medium pressure hose is an EN857 2SC 1/2 bend radius hose with a synthetic rubber tube and cover. This hose is designed with a MSHA flame resistant cover.

Inside Diameter	Part #	Outside Diameter	W. Pressure @ 20°C (70°F)	Bend Radius	Weight (lbs/ft)	Stk	Std Cut Increments	Bulk Length
1/4"	NL329-04	.52"	6500 psi	2.9"	.17	A	50 ft	328 ft
3/8	NL329-06	.67	5300	3.5	.25	A	50	328
1/2	NL329-08	.81	4500	5.1	.35	A	50	328
5/8	NL329-10	.94	4000	6.6	.41	B	50	328
3/4	NL329-12	1.08	3500	7.8	.50	A	50	164
1	NL329-16	1.38	3000	9.8	.74	A	50	164
1-1/4	NL329-20	1.69	2500	12.6	.99	B	50	197
1-1/2	NL329-24	1.97	2000	15.7	1.26	B	50	197
2	NL329-32	2.48	1600	20.8	1.66	C	50	197

Temperature Range: -40°C (-40°F) to +120°C (248°F)

Tube: Black, seamless, oil resistant synthetic rubber.

Cover: Synthetic black, high quality, oil, abrasion and weather resistant rubber.

Reinforcement: Two braid high tensile steel wire.

Typical Ends: • N635 Crimp Series