



Control Equipment Sales, Inc
 Exceptional Sales and Service since 1967

PO Box 2357
 Orland Park, IL 60462

Phone: 708-364-1200
 www.ce1200.com

Shelter Works Quote Request Form

Contact Information:

Name:		Phone:	
Company:		Email:	

Application/Project Description: (E.g. storage site, gas sampling, odorizer, well head, etc.)

Estimated Dimensions: (Note: Additional shipping charge for width over 15.8')

Length:	(typically 2' increments up to 40')
Width:	(typically 2' increments up to 20')
Eave Height:	
Wall Height:	(typically 8', 10', or 12')

Exterior:

(E.g. white, blue, green, tan)

Wall & Roof Insulation:

(Standard R-12 (1.5" closed cell polyiso foam, additional options available))

Wall Reinforcement:

(Standard option 1/2" marine grade ply., additional options available)

Doors: (E.g. gas sampling, odorizer, well head, etc.)

Quantity single 3'x8' door:		Quantity double 6'x8' door:	
Quantity single 4'x8' door:		Quantity double 8'x8' door:	
Optional Lock Features:	(E.g. Three point or anti-panic locking)		

Knock Out Panels or Bulkhead Reinforcements:

(Penetrations for existing pipe or cable)

Floor/Base, Frame/Skid Requirements:

(E.g. no floor, insulated fiberglass, steel frame, aluminum frame, etc.)

HVAC or Heater Requirements:

(E.g. none, window unit, or wall mounted)

Louvered Vent Requirements:

(E.g. 12"x12", 16"x16", 24"x24", etc.)

Skylight Requirements:

(E.g. 12"x12", 24"x24", etc.)

Electrical Requirements:

Classification:	(General purpose or hazardous)
Incoming Service:	(Amps/volts/phase)
Termination:	(Leads to junction box or load center)
Receptacles:	(E.g. 20A duplex, 20A GFCI duplex)
Lighting:	(E.g. interior, exterior, exit sign)

Additional Features/Comments:

Provide Top View Sketch: (Indicate dimensions, doors, and other feature locations if known)