

KEYAMOR



Look for our FSC® certified products!

High Performance Masking Tape

High Performance Masking Tape designed for tough applications. It withstands temperatures up to 212°F (100°C) for 30 minutes, UV rays and humidity. Offers excellent adaptability for curved or irregular surfaces, with strong adhesion and no lifting or curling during use. Ensures sharp lines without smudging and allows easy removal without residue. Suggested removal time: 8 days outdoor and 13 days indoor. FSC®-certified product available upon request.

Backing: Saturated Semi-Crepe Paper

TECHNICAL DATA	KEYAMOR
AVAILABLE COLORS	Orange ●
TOTAL THICKNESS - mm	0.13
TOTAL THICKNESS - mils	5.15

Adhesive: Natural Rubber

Adhesion to Steel (N/25mm - oz/in.): 5.9 / 21

Tensile Strength (N/25mm - lbs/in.): 79 / 18

Elongation at Breakage: 6%

Temperature resistance: up to 212°F (100°C)/30 min

AVAILABLE MEASURES	HAND
WIDTH - mm	12 / 18 / 24 / 36 / 48 / 72
WIDTH - in	0.5 / 0.7 / 0.9 / 1.4 / 1.9 / 2.8
LENGTH - m	55
LENGTH - yd	60

All values provided are typical and do not constitute a guarantee of accuracy, or performance. Applications described are for reference only. Users must evaluate product suitability through testing under actual conditions of use, or otherwise. Proper adhesion require that surfaces be clean, dry and free of grease, oil or other contaminants. Liability is limited to the product's purchase price, consequential damages are excluded. We reserve the right to make changes without obligation in our products and publications.

Storage & Shelf Life:

Store in original packaging, in a cool, dry place (<65% RH) between 15-25°C (59-77°F), away from direct sunlight.

Converted rolls have an expected shelf life of up to 12 months from the date of shipment. For jumbo rolls, the same shelf life applies; however, it is recommended to convert them within 6 months from shipment.