



WASHI PAPER MASKING TAPE

Washi paper tape yellow designed for both internal and external masking. This tape is specifically designed for perfect lines, no bleed through, and clean removal. Resists high temperatures, 248°F (120°C) for 60 minutes, and is waterproof. Ideal for professional and specialized masking applications. Suggested removal time: 60 days outdoor and 90 days indoor.

Backing: Saturated Washi Paper

Adhesive: Acrylic

Available colors: yellow

Temperature resistance: up to 248°F (120°C)/1h

Waterproof: yes

UVR: yes

TECHNICAL DATA	METRIC UNIT	IMPERIAL UNIT	TEST METHOD
Total Thickness	0.09mm	3.54mils	ASTM D3652/PSTC-133
Adhesion To Steel	3.4 N/25mm	12.5 oz/in	ASTM D3330/PSTC-101
Tensile Strength	99 N/25mm	22,4 lbs/in	ASTM D3759/PSTC-131
Elongation at Breakage	5%	5%	ASTM D3759/PSTC-131
Rolling Ball Tack	≤ 3 cm	≤ 1.18 in	ASTM D3121/PSTC-6

AVAILABLE MEASURES

HAND

WIDTH - mm	12 / 18 / 24 / 36 / 48 / 72
WIDTH - in	0.5 / 0.7 / 0.9 / 1.4 / 1.9 / 2.8
LENGTH - m	55
LENGTH - yd	60

All values provided are typical and do not constitute a guarantee of accuracy, or performance. Applications described are for reference only. Users must evaluate product suitability through testing under actual conditions of use, or otherwise. Proper adhesion require that surfaces be clean, dry and free of grease, oil or other contaminants. Liability is limited to the product's purchase price, consequential damages are excluded. We reserve the right to make changes without obligation in our products and publications.

Storage & Shelf Life:

Store in original packaging, in a cool, dry place (<65% RH) between 15-25°C (59-77°F), away from direct sunlight.

Converted rolls have an expected shelf life of up to 12 months from the date of shipment. For jumbo rolls, the same shelf life applies; however, it is recommended to convert them within 6 months from shipment.