



The mark of responsible forestry



The mark of responsible forestry

look for our FSC® certified products!

AUTOMOTIVE MEDIUM MASKING TAPE

Performance Masking Tape designed for excellent adaptability and strong adhesion in the automotive aftermarket, ensuring sharp lines without lifting or curling during work, and preventing smudging due to its resistance to solvents and thinners. It withstands temperatures up to 176°F (80°C)/30 min. Suggested removal time: 5 days indoor. Leaves no residue upon removal. Easily tearable by hand for precise use, minimizing waste. FSC®-certified product available upon request.

Backing: Saturated Semi-Crepe Paper

Adhesive: Natural rubber

Available colors: light yellow

Temperature resistance: up to 176°F (80°C)/30 min

Waterproof: no

UVR: no

TECHNICAL DATA	METRIC UNIT	IMPERIAL UNIT	TEST METHOD
Total Thickness	0.129mm	5.08mils	ASTM D3652/PSTC-133
Adhesion To Steel	5.6 N/25mm	20 oz/in	ASTM D3330/PSTC-101
Tensile Strength	79 N/25mm	18 lbs/in	ASTM D3759/PSTC-131
Elongation at Breakage	6%	6%	ASTM D3759/PSTC-131
Rolling Ball Tack	≤ 3 cm	≤ 1.18 in	ASTM D3121/PSTC-6

AVAILABLE MEASURES

HAND

WIDTH - mm	12 / 18 / 24 / 36 / 48 / 72
WIDTH - in	0.5 / 0.7 / 0.9 / 1.4 / 1.9 / 2.8
LENGTH - m	55
LENGTH - yd	60

All values provided are typical and do not constitute a guarantee of accuracy, or performance. Applications described are for reference only. Users must evaluate product suitability through testing under actual conditions of use, or otherwise. Proper adhesion requires that surfaces be clean, dry and free of grease, oil or other contaminants. Liability is limited to the product's purchase price, consequential damages are excluded. We reserve the right to make changes without obligation in our products and publications.

Storage & Shelf Life:

Store in original packaging, in a cool, dry place (<65% RH) between 15-25°C (59-77°F), away from direct sunlight. Converted rolls have an expected shelf life of up to 12 months from the date of shipment. For jumbo rolls, the same shelf life applies; however, it is recommended to convert them within 6 months from shipment.