



SUNDANCE WOOD STAIN SEALERS PDS

SWSS COLOR SELECTION: No.510 Sundance Gold, No.520 Secretariat Reserve, No.530 Bourbon Barrel Brown, No. 535 Dark Barrel Brown, No.540 Whiskey Falls Teak, No. 550 Cassidy Gang Gray, No.560 Redwood Rose, No.570 Cherry Walnut.

PRODUCT DESCRIPTION:

SUNDANCE WOOD STAIN SEALERS “DECK & TIMBER” and “LOG*1 COAT” are proprietary handcrafted, semi-transparent, high viscosity oil-based stain sealers, They are detailed with high-value long oil alkyd resin-solids, highly refined complex mineral and paraffinic oils, trans-oxide pigmentation content, stoddard solvents, and a fungus inhibitor. Our products are designed to penetrate, protect, extend the life, and enhance the look of all exterior wood. A one-coat-only application to all exterior wood will achieve a beautiful, natural-looking, even wood tone finish!!!

Terrific on new wood, they are especially beneficial on older wood as they will strengthen the wood lignin’s structure and add bulk and flexibility to the wood fiber. The stain sealant components will protect the wood from water damage through cupping, checking, and erosion. It will also protect the wood from U.V. sun damage and mold, and algae build-up.

The products are highly penetrative and will deliver an exceptional even distribution of the stain components into the wood. They will deliver an absolutely uniform, rich, and deep natural-looking wood finish, highlighting the grain of the wood—no drips, blemishes, or steaks. No water-colored look:(All products comply with all state and federal VOC (Volatile Organic Compound) regulations.

PRODUCT USES: Can apply to all porous exterior wood, including Decks, Fences, Log, and Cedar Homes. If you pour water on wood and it doesn’t bead up, it’s ready! *Not recommended for IPE wood.

SURFACE PREP AND APPLICATION METHODS:

SUNDANCE WOOD STAIN SEALERS are penetrating oil-based stain-sealers not meant to create a film-forming layer that will peel or flake away, creating difficult upkeep. *Never apply on a deck that has had an acrylic finish put on it unless totally removed.

They can be applied to all exterior wood, new or old. All wood must be dry and clean, free from any mill glaze, dirt, mold, oxidation, and old finishes. This may require P.W. with cleaner solution, stripping, and or sanding so that wood is clean and absorbent. Once done, it will never need to be done again, except for a P.W. cleaning before re-application of SWS S in years to come.

APPLY: Use only when the wood is dry and temps are the 40s- 90s. Do not apply with expected rain within 24 hours of application. Mix well before and occasionally during application.

The Sundance Stain Sealers can be applied via brush, roller, pad, and or sprayer with a back-roll.

These are a one-application, one-coat product. Apply generously one time while back brushing or rolling. It should initially look like solid paint. Be assured it is not! Wipe up any excess pooling on deck surfaces created from an over application after 24 hours. Failure to do so will cause slow drying tackiness that will not cure into wood. If applying to a board, finish to end.

CLEANING: Use mineral spirits to clean applicators and equipment—soap and water on hands and skin.

STORAGE: Store at temps 40-90 F for up to 2 years, but must be vigorously stirred from bottom to reuse.