

RUPEDL U-ZELE SAE 5W-30 SN

● Description

RUPEDL U-ZELE SAE 5W-30 SN is a high quality synthetic engine oil for passenger car engines. Thanks to the latest technology, it guarantees proper lubrication and effective engine protection. Facilitates engine starting at low temperatures and prevents deposits and carbon deposits inside the engine. It provides excellent antioxidant, anti corrosive and viscosity temperature properties.

RUPEDL U-ZELE SAE 5W-30 SN has high oxidation resistance and cleaning properties, which prevents the formation of deposits on engine components. Thanks to the use of modern technology, it guarantees proper lubrication and effective engine protection. A modern package of enriching additives ensures long and trouble-free service of the car in the most demanding conditions. Provides easy starting at low temperatures.

● Specifications/Recommendations

ACEA C2-16/A1-/B1-12, A5-/B5-12

API SN/CF

PSA B71 2290

Renault RN 0700

● Approvals

Toyota, Mitsubishi

Fiat 9.55 5 35 S1

Subaru, Honda

Mazda, Hyundai

Kia

● Typical Properties

Rupedl U-ZELE SAE 5W-30	Method	Unit	Value
Density at 15°C	DIN 51 757	kg/m³	853
Viscosity at 40°C	DIN 51 562	mm²/s	68,9
Viscosity at 100°C	DIN 51 562	mm²/s	11,64
Viscosity Index	DIN ISO 2909		165
CCS at -35°C	DIN 51 562	mPa.s	5940
Pourpoint	DIN ISO 3016	°C	-39
Flashpoint	DIN ISO 2592	°C	228

*We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.