

RUPEDL P-FRIVE 5W-30

API SN CF 504/507

High Performance Fuel Economy Oil for Passenger Cars of the VW-Group

Description and Properties

RUPEDL P-DRIVE SN/CF C3 504/507 5W-30

is a new fuel-saving SAPS low-friction motor oil, which has been developed especially for VW and Audi engines (with or without extended maintenance intervals). It is optimally tuned to meet the requirements of the latest gasoline and diesel engines as well as their exhaust systems(particulate filter, catalyst).

Advantages:

- Long Life-Service for VW and Audi engines (diesel and petrol) •Optimal protection for catalysts and diesel particulate filters Reduces ash formation in the particulate filter by half

● Backwards compatible with the VW standards 500 00, 501 01, 502 00, 503 00, 503 01,505 00, 505 01, 506 00 and 506 01.

P-Drive 5W-30 cannot be used are the R5 (TDI) and V10 (TDI).

Specifications / Recommendations

API SN	Porsche C-30
ACEA C3	GM Dexos 2
VW504/507	MB-Freigabe 229.51
BMW Longlife-04	

Typical Properties

RUPEDL U-EASA 0W-20-API SP GF-6A	unit	value	method
Density at 15°C	kg/m ³	848	DIN 51 757
Viscosity at 40°C	mm ² /s	71,8	DIN 51 562
Viscosity at 100°C	mm ² /s	11,8	DIN 51 562
Viscosity Index		162	DINISO2909
CCS at -30°C	mPa.s	6200	DIN 51 377
Pourpoint	°C	-45	DINISO3016
Flashpoint	°C	236	DIN ISO2592
TBN	mg KOH/g	6,1	DINISO3771