RUPEDL E-Emerald Automotive Products 9HP

□ Description

E-Emerald 9HP Fluid is an Automatic Transmission Fluid based on HC and PAO.

E-Emerald 9HP has been specially developed for modern ZF 6-, 8- and g-speed automatic transmissions in high-performance vehicles. It is not suitable for use in DCT / DSG or CVT transmissions.

E-Emerald 9HP affords following benefits:

- Highest Quality Features
- High load capacity and extremely wear-reducing
- Superior friction constant
- No foaming Minimal evaporation losses
- Excellent low-temperature switching behavior
- Adapted friction characteristics, for sporty gear changes
- Excellent oxidation and thermal stability
- No effect on usual sealing materials

Specifications/Recommendations

BMW L12108 (83 22 2 152 426)

BMW 83 22 2 305 397

BMW 83 22 2 289 720

Chrysler 68157995AA

Jaguar 02JDE 26444

Land Rover LR 023288

VW / Audi G 060 162 A1/A2/A6, G 055 162 (A2, A6)

ZF Lifeguard fluid 8 (S671 090 312)

Typical Properties

Characteristics	Method	Unit	Value
Density at 15°C	DIN 51 757	kg/m³	844
Color	Visual		green
Viscosity at 40°C	DIN 51 562	mm²/s	26,4
Viscosity at 100°C	DIN 51 562	mm²/s	5,6
Viscosity index	DIN ISO 2909		160
Pourpoint	DIN ISO 3016	°C	-45
Flashpoint	DIN ISO 2592	°C	226

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development...

