

RUPEDL S-5156 UHPD

SAE 15W-40

TYPE Truck Engine Oil

■ Description

Rupedl S-5156 UHPD SAE 15W-40 is a Synthetic Ultra High-Performance Diesel (UHPD) engine oil that satisfies the strictest standards of the truck producers. Thanks to its unique consistence has perfect viscosity temperature properties that guarantee easy cranking at extremely low temperatures and safe protection from wear-out at high loads and temperatures.

■ Specifications/Recommendations

API CJ-4/SN
ACEA E7, E9
JASO DH-2
CATERPILLAR ECF-3
CUMMINS CES 20081
DETROIT DIESEL 93K218
DEUTZ DQC III-10 LA
MACK EO-O Premium Plus
MAN M 3575
MB 228.31
RENAULT RLD-3
SCANIA Low Ash
VOLVO VDS-4

■ Typical Properties

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/m ³	872
Dynamic viscosity at -20 °C	D 5293	mPa·s	6250
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-40
TBN	D 2896	gKOH/kg	9,82
Viscosity at 100 °C	D 445	CSt	14,26
Viscosity at 40 °C	D 445	CSt	102,20
Viscosity index	D 2270		142

