

# RUPEDL E-Topaz

## Automotive Products

# IIIH

### Description

**E-Topaz IIH** fluid is an Automatic Transmission Fluid, which is made from mineral base oils and products from the synthesis technology, in combination with a special additive package.

**E-Topaz IIH** is used in automatic vehicle gears, servo steering, fluid couplings and hydrodynamic converters as well as in hydraulics of passenger cars, commercial vehicles, busses and construction vehicles, if an ATF of Dexron IIH - type is recommended.

**E-Topaz IIH** affords following benefits:

- Optimally balanced frictional behavior
- Very good wear protection
- Excellent cold fluidity
- Outstanding oxidation stability
- Good corrosion- and rust preventive properties
- Low foaming tendency and best elastomer compatibility

### Specifications/Recommendations

DEXRON III H und Dexron III G

MB 236.1, 236.5, 236.6 & 236.7

MAN 339 Typ Z1 & V1, Z2 & V2

Volvo 97340, 97341

Voith 55.6335 & 55.6336

ZF TE-ML 02F, 04D, 09,11A, 14A & 17C

Allison C-4 Allison TES, 389

Ford Mercon Ford M2C138-CJ, M2C 166-H

### Typical Properties

Characteristics	Method	Unit	Value
Density at 15°C	DIN 51 757	kg/m <sup>3</sup>	851
Viscosity at 40°C	DIN 51 562	mm <sup>2</sup> /s	40
Viscosity at 100°C	DIN 51 562	mm <sup>2</sup> /s	8,1
Viscosity index	DIN ISO 2909		182
Pourpoint	DIN ISO 3016	°C	-50
Flashpoint	DIN ISO 2592	°C	220

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.