

RUPEDL U-NALA 0W-20

● Description

RUPEDL U-NALA 0W-20 is a fully synthetic low friction oil to be used in passenger cars gasoline and diesel engines. The special formulation assures maximum thermal and mechanical stability, excellent viscosity temperature dependency and low evaporation loss. The low friction properties of the used synthetic base stocks provide in conjunction with the most modern anti-friction additives noticeable reduction of fuel consumption and thus for protection of environment by decreasing pollution.

RUPEDL U-NALA 0W-20 grants maximum wear protection and features best low temperature properties. These assure fast oil provision at all lubrication areas and minimize cold starting wear. Highly effective dispersant additives prevent sludge built up in the oil circuit and deposits on piston and inlets valves. The compatibility is assured when used with elastomers and when used in engines.

● Specifications/Recommendations

ACEA A1-/B1 12

VW 508 00 / 509 00

VW TL 52577

● Typical Properties

Rupedl U-NALA 0W-20	Method	Unit	Value
Density at 15°C	DIN 51 757	kg/m ³	836
Viscosity at 100°C	DIN 51 562	mm ² /s	8,1
CCS at -35°C	DIN 51 562	mPa.s	3980
Pourpoint	DIN ISO 3016	°C	-54
Flashpoint	DIN ISO 2592	°C	234
TBN	DIN ISO 3771	Mg KOH/g	8,0

*We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.