

RUPEDL U-NELA 5W-20

● Description

RUPEDL U-NELA 5W-20 is a modern, premium class engine oil for the lubrication of all four-stroke engines of Japanese, Korean and American light vehicles, minivans and SUVs. Ideal for up-to-date petrol engines with direct injection, turbochargers and variable valve timing (VTEC, VVT-i, VTC, CVVT, VVL, VVTIL-i, MIVEC etc.).

The combination of unconventional base oils together with the latest additive technology guarantees an engine oil that provides exceptional protection against wear and keeps the engine clean while ensuring fast and reliable oil penetration. Specially recommended for Honda, Acura, Mazda, Mitsubishi, Ford, Chrysler, Hyundai, Kia, Isuzu, Suzuki, Toyota, Nissan, Subaru and GM.

● Specifications/Recommendations

API SN

ILSAC GF-5

FORD WSS-M2C945-A

FORD WSS-M2C945-B

FORD WSS-M2C930-A

FORD WSS-M2C925-A

FORD WSS-M2C948-B

GM dexos1

● Typical Properties

Rupedl U-NELA 5W-20	Method	Unit	Value
Density at 15°C	ASTM D-1298	kg/l	0.85
Viscosity at 100°C	ASTM D-445	cSt	7.69
Viscosity at 40°C	ASTM D-445	cSt	40.07
Viscosity Index	ASTM D-2270		165
CCS at -30°C	ASTM D-5293	mPa.s	5645
Pourpoint	ASTM D-97	°C	-45
Flashpoint	ASTM D-92	°C	224
TBN	ASTM D-2896	mg KOH/g	8.44

*We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.