

RUPEDL 4T SAE 15W-50

Four Stroke Oils For Motorcycles

Description

RUPEDL 4T SAE 15W50 is a high performance special engine oil for motor cycles with air- and water-cooled 4-stroke engines of highest output. It is the ideal partner for all sportive motor-cycles, on all roads and off-road. The high capacity is assured by a combination of high quality base oils with successfully tested additives.

RUPEDL 4T SAE 15W50 offers

- Optimal lubrication in motor and in gear and assured functionality of wet clutches even at extreme operation conditions and continuous use.
- Outstanding motor cleanliness, especially at pistons and valves.
- Highest wear protection of all power transmission components in motor and gear.
- All-seasons use at temperate climate

Specifications/Recommendations

ACEA A3-04
API SN
JASO MA2

Typical Properties

Characteristics	Method	Unit	Value
Density at 15°C	DIN 51 757	kg/m ³	872
Viscosity at 40°C	DIN 51 562	mm ² /s	138
Viscosity at 100°C	DIN 51 562	mm ² /s	19,1
Viscosity index	DIN ISO 2909		157
Dynam. Viscos. at -25°C	DIN 51 377	mPa.s	5740
Pourpoint	DIN ISO 3016	°C	-36
Flashpoint	DIN ISO 2592	°C	226
TBN	DIN ISO 3771	mg KOH/g	10.5

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.

