

RUPEDL U-055MF 5W-50 SN/MA2

FULLY SYNTHETIC LOW FRICTION OIL Product Description

Description

RUPEDL U-055MF 5W-50 SN/MA2

is a fully synthetic high performance motor oil to be used in passenger cars and light-duty commercial vehicles. It is engineered with a blend of synthetic base stocks and a most modern additive system, and thus it meets the strongest requirements of 4-stroke gasoline-, diesel-, naturally aspirated and turbocharged engines. It is used in vehicles with catalytic converter as well, of course

Advantages:

affords most possible engine protection by stable lubricating film even under extreme operating temperature excellent cold start and fast oil feed even at temperatures until -30°C assure fuel- and oil-economy.

very good dispersancy anticipates oil sludge forming. optimized high temperature viscosity to meet newest requirements of leading car manufacturers

Specifications/Recommendations

API SN/CF
ACEA A3/B4

JASO
MA2

Typical Properties

RUPEDL U-055MF 5W50	unit	value	method
Density at 15°C	kg/m ³	855	DIN 51 757
Viscosity at 40°C	mm ² /s	105	DIN 51 562
Viscosity at 100°C	mm ² /s	17,2	DIN 51 562
Viscosity Index		173	DIN ISO 2909
CCS at -30°C	mPa.s	6310	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	222	DIN ISO 2592
TBN	mg KOH/g	14,8	DIN ISO 3771