RUPEDL U-020C5 SAE 0W20 SP C5

Description

RUPEDL U-020C5 SAE 0W-20 GF-6 C5 is a modern low friction oil with an advanced performance, providing excellent wear protection and above-average cleaning power. It contributes to the service life extension of exhaust-aftertreatment systems and redounds to their trouble-free operation.
RUPEDL U-020C5 SAE 0W-20 GF-6 C5 is produced on base of the highest quality components, which are currently available. The product ist completely compatible with the newest diesel particulate filters (DPF) and with catatytic converters of gasoline engines. It combines outstanding performance with excellent motor protection and improves the reduction of fuel consumtion.

RUPEDL U-020C5 SAE 0W-20 GF-6 C5 provides

- **contribution in the reduction of particle built-up on the diesel particulate filter by its low ash content**
- **reduction of the danger of poisoning on catalytic converters of gasoline engines by its low sulphur**
- **and low phosphorus amounts.**
- **reduction of deposits and sludge by effective cleaning additives**
- **extented oil drain intervals, because of decelerated oil aging by outstanding thermic stability**

Specifications/Recommendations

API SP	ACEA C5
ILSAC GF-6A	BMW Longlife 17 FE+
FORD WSS-M2C947-B1	MB-Freigabe 229.71

Typical Properties

RUPEDL U-020Q7 0W20 GF-7	unit	value	method
Density at 15°C	kg/m³	846	DIN51 757
Viscosity at 40°C	mm²/s	41.9	DIN51 562
Viscosity at 100°C	mm²/s	8.1	DIN51 562
Viscosity Index		172	DIN51 377
CCS at -35°C	mPa.s	6050	DIN 51 377
Pour point	°C	-49	DINISO3016
Flash point	°C	230	DINIS02592
TBN	mg KOH/g	7.6	DINISO3771