

RUPEDL P4141 UHPD

Motor Oil For Trucks/Buses SAE 10W-40 CI-4

■ Description

Rupedl P4141 UHPD 10W-40 is a high performance engine oil, which is made from base oils of the most modern synthesis technology. It is suitable for each kind of diesel engines in commercial cars, especially for EURO 4- and - 5- motors.

Rupedl P4141 UHPD 10W-40 assures top performance in many quality criterions :

- Easy low-wear cold-start by good fluidity, even at low temperatures.
- Excellent aging and corrosion protection.
- Exceeding wear protection and cleaning power.
- Allows the most extended oil drain intervals which car producers recommend.
- Outstanding thermal oxydative stability and low evaporation tendency.
- High performance additives and the synthetic base care for unexcelled performance.

■ Specifications/Recommendations

ACEA E4 / E7

API CI-4 + UHPD

Caterpillar ECF 1-a, ECF 2

Cummins CES 20076, 20077, 20078

Deutz DQC IV-10

Global DHD-1

Iveco (if recommended for ACEA E4 / E7-08)

MACK EO-M+

■ Approvals

MB 228.3 / 229.1

MAN M 3275

VOLVO VDS-3

Mack EO-N Renault

VI RLD-2

■ Typical Properties

Characteristics	Method	Unit	Value
Density at 15°C	DIN 51 757	kg/m ³	863
Viscosity at 40°C	DIN 51 562	mm ² /s	94,0
Viscosity at 100°C	DIN 51 562	mm ² /s	14,2
Viscosity index	DIN ISO 2909		156
CCS at -25°C	ASTM D5293	mPa.s	6380
Pourpoint	DIN ISO 3016	°C	-36
Flashpoint	DIN ISO 2592	°C	224
TBN	DIN ISO 3771	mg KOH/g	12,7

